


# FP-710(Beta)

AMD® Ryzen™, Ryzen™ AI 8000 Series Processor


“Zen 4” Architecture based Mini ITX with 4 DisplayPorts



## Features

- CPU: AMD Ryzen™ 8845HS PRO Processor
- Memory: Dual channel SO-DIMM DDR5 up to 96GB
- Display: AMD Radeon™ Graphics, Up to 4 independent 4K displays
- Ethernet: Realtek® RTL8111H(1.0GbE)+RTL8125(2.5GbE)
- Storage: 2xM.2\_2280 Slot for NVMe
- Expansion: PCIe 4X, M.2 for Wi-Fi
- Power: DC-IN Jack

**AMD**  
together we advance\_



## Introduction

The Maxtang FP-710 Mini-ITX motherboard is powered by AMD Ryzen™ 7 8845HS Pro processor, offering up to 8 cores and 16 threads based on the advanced “Zen 4” architecture. With integrated AMD Ryzen™ AI technology and a dedicated Neural Processing Unit (NPU), it delivers powerful AI processing for enhanced productivity, creativity, and next-gen PC experiences. Designed for high performance and energy efficiency, the FP-710 is an ideal solution for a wide range of embedded applications.

This compact Mini ITX motherboard supports up to 96GB DDR5 memory via 2x SO-DIMM slots, 4x DisplayPort 1.4 outputs for four independent 4K displays, dual M.2 2280 slots for NVMe storage, and an M.2 2230 slot for Wi-Fi. It also offers optional TPM support for improved security with a rich set of I/O ports, including 6x COM, 8x USB, GPIO, Line-out, and Mic-in. Whether for electronic gaming, digital signage, or medical imaging, the FP-710 delivers the performance and connectivity modern industries demand.



H/W Monitor



Watchdog





GPIO



Brightness

## I/O Interfaces



\*Please Note!!


This board does not support SATA for storage.

## Technical Specifications

Processor	CPU	Ryzen™ 7 8845HS Pro
	Cores/Threads	8C/16T
	Max. Boost Clock	Up to 5.1 GHz
	Base Clock	3.8 GHz
	L2/L3 Cache	8MB/16MB
AI Capabilities	AMD Ryzen™ AI	Available
	BIOS	AMI SPI BIOS
Memory	Type	Dual Channel SO-DIMM DDR5
	Max. Capacity	96GB
Display	GPU	AMD Radeon™ 780M Graphics
		Four 4K Displays. Resolution up to 4096x2160 for single displays.
	Interface	4 xDP1.4
Ethernet	Controller	Realtek® RTL8111H. Max.Speed:10/100/1000Mbps
		Realtek® RTL8125. Max.Speed:10/100/1000/2500Mbps
	Interface	2xRJ45
Audio	Audio Codec	Realtek® ALC897 High-definition Audio Codec
	Interface	1xLine-out, 1xMic-in, support audio header and amplifier header
Hardware		CPU system temperature, onboard voltage, watchdog
Storage	M.2_N	2xM.2_2280 Slot for NVMe SSD
Expansion	M.2_E	1xM.2_2230 Slot for Wi-Fi and Bluetooth
	PCIe 4X	1
Other I/O	COM	6xRS232 (COM2 can be set as RS485 through hardware changes)
	USB3.2	2
	USB2.0	6 (2*Port + 4*header)
	GPIO	8-bit
	Buzz_M	Yes
	TPM2.0	Onboard, Optional
Dimension	Form Factor	Mini ITX
	Size	170 mm x 170 mm
Power	Standard Port	DC-IN Jack (Version 1: 19V / Version 2: 12V)
Temperature	Operating Temp.	-20°C ~60°C
	Storage Temp.	-40°C ~80°C
Operating System		Windows 10/11 64bit, Linux 64bit

\*Image is for reference only. This board does not support SATA for storage. \*All specifications and photos are subject to change without notice.

## Functional Block Diagram



## Order Information

Model Name	Description
DT8845HS-PRO1	DT AMD 8845HS PRO FP710 DDR5 2LAN(8111H+8125) 6COM 4DP PCIE4X NVME 12V
DT8845HS-PRO2	DT AMD 8845HS PRO FP710 DDR5 2LAN(8111H+8125) 6COM 4DP PCIE4X NVME 19V

\*For customization, please contact your regional sales representative. Confirm model details before purchase, as they may vary.

Copyright © 2025 Maxtang Technology Co. Ltd. All rights reserved. All data is for information purposes only and not guaranteed for legal purposes. Information has been carefully checked and is believed to be accurate; however, no responsibility is assumed for inaccuracies. Maxtang and the Maxtang logo and all other trademarks or registered trademarks are the property of their respective owners and are recognized.